# RAGE8 CXP





8"/203MM

**500W** MAX power

**93 DB**Sensitivity

70-20000HZ Frequency Response

2.5"/63.5MM Aluminium voice coi

## **ELECTRO ACOUSTIC SPECIFICATIONS**

8/203 in/mm
500 Watts
250 Watts
4 Ohm
69.4 Hz
70-20000 Hz
93dB
1.75"/44mm
2.5"/63.5mm
ALUMINIUM
50 Oz

## MOUNTING / SHIPPING INFORMATION

Overall Diameter	8.4/214 in/mm
Bolt Circle Diameter	7.6/194 in/mm
Baffle cutout Diameter	7.2/184 in/mm
Depth	4.7/120 in/mm
Net Weight(1 PC)	4.5 kgs
Shipping Weight(1PC)	5.0 kgs
Shipping Box(1PC)	24x24x17 cm

### THIELE SMALL PARAMETERS

FS	69.4 Hz
Vas	14.2 L
REOhms	3.4ohm
Qms	5.13
Qes	0.723
Qts	0.64
BL	16.4
MMS	25.7 grams
Xmax(mm)	4 mm
Sd(cm <sup>2</sup> )	213 cm <sup>2</sup>
Effici ency%	0.6%
Le(1k Hz)	0.76 mH
EBP	96

#### FREOUENCY RESPONSE DATA

